



SAFETY DATA SHEET

Diesel Recovery

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200 and WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as amended) and the requirements of the Hazardous Product Regulations (HPR).

1. Identification

Product identifier

Product name Diesel Recovery

Product number DRC

Recommended use of the chemical and restrictions on use

Application Fuel additive.

Uses advised against Avoid the formation of mists.

Details of the supplier of the safety data sheet

Supplier AMSOIL INC.
Bordner, Ladner, Gervais
Scotia Plaza, 40 King St W
Toronto, ON, Canada M5H 3Y4
T: +1 416-367-6547

Manufacturer AMSOIL INC.
One AMSOIL Center,
Superior, WI 54880, USA.
T: +1 715-392-7101
compliance@amsoil.com

Emergency telephone number

Emergency telephone CHEMTREC: Within USA and Canada: 1-800-424-9300
Outside the USA and Canada: +1 703-741-5970
(collect calls accepted) 24/7

2. Hazard(s) identification

Classification of the substance or mixture

OSHA/WHMIS Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard and according to the hazard criteria of the Hazardous Product Regulations.

Physical hazards Flam. Liq. 3 - H226

Health hazards Carc. 2 - H351 STOT SE 3 - H336 STOT RE 1 - H372 Asp. Tox. 1 - H304

Environmental hazards Aquatic Acute 3 - H402 Aquatic Chronic 3 - H412

Label elements

Pictogram



Signal word

Danger

Diesel Recovery

Hazard statements

H226 Flammable liquid and vapor.
 H304 May be fatal if swallowed and enters airways.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
 P240 Ground/ bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing vapor/ spray.
 P264 Wash contaminated skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves, eye and face protection.
 P301+P310 If swallowed: Immediately call a poison center/ doctor.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P308+P313 If exposed or concerned: Get medical advice/ attention.
 P312 Call a poison center/ doctor if you feel unwell.
 P331 Do NOT induce vomiting.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

Hydrogenated base oil, Hydrogenated base oil, Naphthalene

Other hazards

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

Hydrogenated base oil	50 - 90%
CAS number: 8052-41-3	
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
STOT RE 1 - H372	
Asp. Tox. 1 - H304	

Diesel Recovery

Hydrogenated base oil	5 - <10%
CAS number: 64742-94-5	
Classification	
Skin Irrit. 2 - H315	
STOT SE 3 - H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	
1,2,4-Trimethylbenzene	1 - <2.5%
CAS number: 95-63-6	
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2A - H319	
STOT SE 3 - H335	
Aquatic Chronic 2 - H411	
Naphthalene	0.5 - <1%
CAS number: 91-20-3	
M factor (Acute) = 1	
M factor (Chronic) = 1	
Classification	
Acute Tox. 4 - H302	
Carc. 2 - H351	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

Composition comments The exact percentage is withheld as a trade secret in accordance with 29 CFR 1910.1200.

4. First-aid measures

Description of first aid measures

General information	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
Ingestion	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.

Diesel Recovery

Skin Contact	Wash skin thoroughly with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Symptoms following overexposure may include the following: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	Prolonged contact may cause dryness of the skin.
Eye contact	May cause temporary eye irritation.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.
---	--

Diesel Recovery

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves, that provides a basic level of protection during chemical incidents is defined by the Canada Occupational Health and Safety Regulations, by provincial guidelines on occupational health and safety or by NFPA standards if applicable.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of vapors and spray/mists. Use suitable respiratory protection if ventilation is inadequate.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Approach the spillage from upwind. Small Spillages: Absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Diesel Recovery

Usage precautions	Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. In use may form flammable/explosive vapour-air mixture. Vapors may accumulate on the floor and in low-lying areas. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Avoid discharge to the aquatic environment. Do not handle broken packages without protective equipment. Do not reuse empty containers. Avoid contact with used product.
Advice on general occupational hygiene	Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Conditions for safe storage, including any incompatibilities

Storage precautions	Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Eliminate all sources of ignition. Take precautionary measures against static discharges. Ground container and transfer equipment to eliminate sparks from static electricity. Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.
Storage class	Flammable liquid storage.

Specific end uses(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.
----------------------------	---

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

Comments	The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.
-----------------	--

Hydrogenated base oil

Long-term exposure limit (8-hour TWA): OSHA 500 ppm 2900 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 100 ppm 525 mg/m³

1,2,4-Trimethylbenzene

Long-term exposure limit (8-hour TWA): ACGIH 25 ppm 123 mg/m³

Naphthalene

Long-term exposure limit (8-hour TWA): OSHA 10 ppm 50 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 10 ppm 52 mg/m³

A3, DSens, Sk

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

DSens = Dermal sensitizer.

Sk = Danger of cutaneous absorption.

Hydrogenated base oil (CAS: 8052-41-3)

Diesel Recovery

Immediate danger to life and health 20,000 mg/m³

Naphthalene (CAS: 91-20-3)

Immediate danger to life and health 250 ppm

Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.6), and any relevant provincial regulation relating to health and safety at work. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.9), and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Gas and combination filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134 and/or the Canadian regulation on health and safety at work, SOR/86-304, Part XII (12.7), and any relevant provincial regulation relating to health and safety at work.

Diesel Recovery

Environmental exposure controls Keep container tightly sealed when not in use.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Amber.
Odor	Mild hydrocarbon.
Odor threshold	Not available.
pH	Not available.
Melting point	-70°C/-94°F Estimated value.
Initial boiling point and range	157.2°C/315°F Estimated value.
Flash point	43.3°C/110°F Tag closed cup.
Evaporation rate	Slow.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.7% Upper flammable/explosive limit: 6.8%
Vapor pressure	0.9 hPa Estimated value.
Vapor density	> 4
Relative density	0.79
Solubility(ies)	Not known.
Partition coefficient	Not available.
Auto-ignition temperature	232.2°C/450°F Estimated value.
Decomposition Temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not considered to be explosive.
Oxidizing properties	Does not meet the criteria for classification as oxidizing.
Volatility	98% Estimated value.

10. Stability and reactivity

Reactivity	See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidizing agents.
Conditions to avoid	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented. Do not pressurize, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition.

Diesel Recovery

Materials to avoid	Oxidizing materials. Acids - oxidizing.
Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 550.0

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

Contains a substance which may be potentially carcinogenic. IARC Group 2B Possibly carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H336 May cause drowsiness or dizziness.

Target organs

Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure STOT RE 1 - H372 Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Aspiration hazard

Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

Diesel Recovery

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Symptoms following overexposure may include the following: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.
Ingestion	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin Contact	Prolonged contact may cause dryness of the skin.
Eye contact	May cause temporary eye irritation.
Route of exposure	Ingestion Inhalation Skin and/or eye contact
Target Organs	Central nervous system

Toxicological information on ingredients.

Hydrogenated base oil

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 590.0

Species Rat

ATE inhalation (vapours mg/l) 590.0

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 24 hours, Rabbit Erythema/eschar score: Moderate to severe erythema (3). Edema score: Slight oedema - edges of area well defined by definite raising (2).

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 1 minute, Rabbit Not irritating.

Skin sensitization

Skin sensitization Buehler test - Guinea pig: Not sensitizing.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative.

Diesel Recovery

Genotoxicity - in vivo	Chromosome aberration: Negative.
<u>Carcinogenicity</u>	
Carcinogenicity	LOAEL 250 mg/kg/day, Dermal, Mouse No evidence of carcinogenicity in animal studies.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Fertility - NOAEL 750 mg/kg/day, Oral, Rat P
Reproductive toxicity - development	Embryotoxicity: - NOAEL: 1000 mg/kg/day, Oral, Rat
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	May cause drowsiness or dizziness.
Target organs	Central nervous system
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEL 750 mg/kg/day, Oral, Rat NOAEC >= 24 mg/m ³ , Inhalation, Rat
<u>Aspiration hazard</u>	
Aspiration hazard	Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

1,2,4-Trimethylbenzene

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	6,000.0
Species	Rat
Notes (oral LD₅₀)	REACH dossier information. Based on available data the classification criteria are not met.
ATE oral (mg/kg)	6,000.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	3,440.0
Species	Rat
Notes (dermal LD₅₀)	REACH dossier information. Read across data. Based on available data the classification criteria are not met.
ATE dermal (mg/kg)	3,440.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	10.2
Species	Rat
Notes (inhalation LC₅₀)	REACH dossier information. Read across data. Harmful if inhaled.
ATE inhalation (vapours mg/l)	10.2

Diesel Recovery

Skin corrosion/irritation

Animal data Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2). REACH dossier information. Read across data. Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.2 ml, 1 second, Rabbit REACH dossier information. Read across data. Slightly irritating.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Guinea pig maximization test (GPMT) - Guinea pig: Not sensitizing. REACH dossier information. Read across data. Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Based on available data the classification criteria are not met.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Developmental toxicity: - NOAEC: 1470 mg/m³, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335 May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 600 mg/kg, Oral, Rat REACH dossier information. Read across data. Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard 0.63 cSt @ 50°C/122°F REACH dossier information. Not anticipated to present an aspiration hazard, based on chemical structure.

12. Ecological Information

Toxicity Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

Ecological information on ingredients.

Hydrogenated base oil

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: 2 - 5 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: 1.4 mg/l, Daphnia magna

Diesel Recovery

Acute toxicity - aquatic plants	EL ₅₀ , 24 hours: 1 - 3 mg/l, Pseudokirchneriella subcapitata
<u>Chronic aquatic toxicity</u>	
NOEC	
Degradability	--
Chronic toxicity - fish early life stage	NOEL, 28 days: 0.098 mg/l, Oncorhynchus mykiss (Rainbow trout) QSAR model
Chronic toxicity - aquatic invertebrates	EL ₅₀ , 21 days: 0.89 mg/l, Daphnia magna

1,2,4-Trimethylbenzene

Toxicity	Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.
<u>Acute aquatic toxicity</u>	
Acute toxicity - fish	LC ₅₀ , 96 hours: 7.72 mg/l, Pimephales promelas (Fat-head Minnow) REACH dossier information.
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 3.6 mg/l, Daphnia magna REACH dossier information.
Acute toxicity - aquatic plants	EC ₅₀ , 96 hours: 2.356 mg/l, Freshwater algae REACH dossier information. QSAR model

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Hydrogenated base oil

Biodegradation	Water - Degradation 61 %: 28 days Readily biodegradable but failing the 10-day window.
-----------------------	---

1,2,4-Trimethylbenzene

Persistence and degradability	The product is readily biodegradable.
Phototransformation	Water - DT ₅₀ : 12 hours REACH dossier information.
Biodegradation	Water - Degradation 75%: 5 days

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

Hydrogenated base oil

Diesel Recovery

Bio-Accumulative Potential Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

1,2,4-Trimethylbenzene

Bio-Accumulative Potential BCF: 243, Pimephales promelas (Fat-head Minnow) QSAR model REACH dossier information.

Partition coefficient log Kow: 3.65 REACH dossier information.

Mobility in soil

Mobility No data available.

Ecological information on ingredients.

Hydrogenated base oil

Mobility Volatile.

1,2,4-Trimethylbenzene

Mobility The product is partly soluble in water and may spread in the aquatic environment.

Adsorption/desorption coefficient Soil - log Koc 3.04 REACH dossier information. QSAR model

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. Transport information

General

For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

UN Number

UN No. (TDG) UN1268

UN No. (IMDG) UN1268

UN No. (ICAO) UN1268

Diesel Recovery

UN No. (DOT) UN1268

UN proper shipping name

Proper shipping name (TDG) PETROLEUM DISTILLATES, N.O.S. (CONTAINS HYDROGENATED BASE OIL, 1,2,4-TRIMETHYLBENZENE)

Proper shipping name (IMDG) PETROLEUM DISTILLATES, N.O.S. (CONTAINS HYDROGENATED BASE OIL, 1,2,4-TRIMETHYLBENZENE)

Proper shipping name (ICAO) PETROLEUM DISTILLATES, N.O.S. (CONTAINS HYDROGENATED BASE OIL, 1,2,4-TRIMETHYLBENZENE)

Proper shipping name (DOT) PETROLEUM DISTILLATES, N.O.S. (CONTAINS HYDROGENATED BASE OIL, 1,2,4-TRIMETHYLBENZENE)

Transport hazard class(es)

DOT hazard class 3

DOT hazard label 3

TDG class 3

TDG label(s) 3

IMDG Class 3

ICAO class/division 3

DOT transport labels



Transport labels



Packing group

TDG Packing Group III

IMDG packing group III

ICAO packing group III

DOT packing group III

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

EmS F-E, S-E

DOT reportable quantity RQ: Naphthalene (11111.1111 lbs)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Diesel Recovery

15. Regulatory information

Regulatory References OSHA Hazard Communication Standard 29 CFR §1910.1200 Hazardous Products Regulation (SOR/2015-17) Transportation of Dangerous Goods Regulations -SOR/2015-100.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

Naphthalene

Final CERCLA RQ: 100(45.4) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

Naphthalene

0.1 %

1,2,4-Trimethylbenzene

1.0 %

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

The following ingredients are listed or exempt:

Naphthalene

Known to the State of California to cause cancer.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

Naphthalene

1,2,4-Trimethylbenzene

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

Hydrogenated base oil

Naphthalene

Diesel Recovery

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

Hydrogenated base oil

Naphthalene

1,2,4-Trimethylbenzene

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

Hydrogenated base oil

Naphthalene

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Hydrogenated base oil

Naphthalene

1,2,4-Trimethylbenzene

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

Hydrogenated base oil

Naphthalene

1,2,4-Trimethylbenzene

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

Hydrogenated base oil

Naphthalene

1,2,4-Trimethylbenzene

Inventories

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

Diesel Recovery

Abbreviations and acronyms used in the safety data sheet	C.A.S. = Chemical Abstracts Service; E.C. No = European Commission number; GHS = Globally Harmonised System; OSHA = Occupational Safety and Health Administration; WHMIS = Workplace Hazardous Materials Information System; DOT = Department of Transport; TDG = Transport of Dangerous Goods Regulations; IMDG = International Maritime Dangerous Goods; IATA = International Air Transport Association; SARA = Superfund Amendments and Reauthorization Act; CERCLA = Comprehensive Environmental; EPCRA = Emergency Planning and Community Right-to-Know Act; TSCA = Toxic Substances Control Act; LD/LC/EC = Lethal Dose, Lethal Concentration/Effect Concentration for 50% of population; NOEC = No Overall Effect Concentration; NOEL = No Overall Effect Level; REACH = Registration, Evaluation, Authorisation & Restriction of Chemicals; STOT-RE = Single Target Organ Toxicity - Repeat Exposure; STOT-SE = Specific Target Organ Toxicity - Single Exposure; PBT = Persistent, Bioaccumulative, Toxic; vPvB = Very Persistent, Very Bioaccumulative.
Classification abbreviations and acronyms	Flam. Liq. = Flammable liquid Carc. = Carcinogenicity Asp. Tox. = Aspiration hazard STOT RE = Specific target organ toxicity-repeated exposure STOT SE = Specific target organ toxicity-single exposure Aquatic Chronic = Hazardous to the aquatic environment (chronic)
Key literature references and sources for data	Source: European Chemicals Agency, http://echa.europa.eu/
Training advice	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
Revision comments	This is the first issue.
Revision date	5/9/2018
SDS No.	7488
Hazard statements in full	H226 Flammable liquid and vapor. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure. H372 Causes damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H402 Harmful to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.